

Instructions for Service Kit FK105693 Ignition Wire Retrofit for 24CGA10

IMPORTANT: The Installation of this adapter must be performed by qualified Cleveland Range authorized technicians.

IMPORTANT: Read the entire installation procedure before beginning the installation of this kit.

Parts List for SERVICE KIT, IGNITION WIRE RETROFIT, 24CGA10 P/N FK105693		
Part Number	Description	Quantity Each
105693	MODULE, SPARK CONTROL	1
300641	TERMINAL, FLAG, SLIP-ON	1
300532002000	HEAT SHRINK TUBE, 2.00"	1

Installation Procedure Ignition Wire Retrofit Kit

1. Turn OFF the steamer and allow it to cool.
2. Turn OFF the electricity at the Main External Power Switch, turn OFF the water supply, and turn OFF the gas at the Main Manual Gas Valve.
3. Remove the drip tray assembly.
4. Open the control box.
5. Detach the ignition wire from the old spark control module
6. Remove the old spark control module.
7. Install the new spark control module.
8. Cut the old terminal from the ignition wire.
9. Slip the heat shrink tubing over the ignition wire.
10. Strip the ignition wire and attach the flag terminal.
11. Slip the heat shrink tubing over the end of the flag terminal.
12. Shrink the heat shrink tubing with a heat gun.
13. Attach the flag terminal to the new spark control module.
14. Close the control box and replace the drip tray.
15. Turn ON the utilities and restart the steamer as usual.

1333 East 179th Street
Cleveland, Ohio 44110
Phone: (216) 481-4900
Fax: (216) 481-3782
www.clevelandrange.com

