

# AIR PAC



*Model #AP4*

## Specification:

Four individually controlled all-purpose deck ovens in a compact stack design. Each oven utilizes a unique energy delivery system of controlled hot air flow for fast, consistent operation. Offers minimum preheat time, consistent selected temperatures, high quality production and menu versatility. Available in 208 or 240 volt - 3 Phase only. Two circuits required.



## Standard Features:

- Stainless steel front, sides, top, and legs
- Four Heavy-duty pull-down front doors
- Removable bottom jet plate
- Adjustable steel wire oven rack (2 positions) one per-deck
- Electronic controls with precision timers
- Single speed fan with ¼ HP motor (0.5 kW)
- 4.7 kW element package per deck
- Leveling and front-locking casters
- 1 year limited parts & labor warranty on ovens

## Optional Features:

- Extra Stainless Steel wire rack (s)
- Perforated stainless steel pizza deck, adjustable (two positions)

*Note: Ovens supplied with casters must be installed with an approved restraining device.*

Garland Commercial Industries, Inc.  
185 East South Street  
Freeland, Pennsylvania 18224  
Phone: (570) 636-1000  
Fax: (570) 636-3903

Garland Commercial Ranges Ltd  
1177 Kamato Road, Mississauga, Ontario  
L4W 1X4 CANADA  
Phone: 905-624-0260  
Fax: 905-624-5669

Enodis UK LTD  
Swallowfield Way, Hayes, Middlesex  
UB3 1DQ ENGLAND  
Telephone: 081-561-0433  
Fax: 081-848-0041



Item #: \_\_\_\_\_  
 Model: AP4  
 Product Name: Electric Four Compartment Deck Oven

Oven Interior Dimensions*			Exterior Dimensions			Shipping Wt. Lbs./Kg	
Width	Height	Depth	Width	Height	Depth	Crated	Uncrated
19-1/4" (489mm)	4-3/4" (121mm)	17-3/4" (451mm)	36-1/2" (927mm)	64-3/4" to 66" (1145mm) to (1676mm)	34-1/4" (870mm)	800/363	650/295

\*With rack or pizza deck in place Two fixed rack positions: 1-1/8" (28mm) and 1-5/8" (41mm)

Installation Notes				
Combustible Wall Clearance			Entry Clearance	
Left	Right	Rear	Crated	Uncrated
0" (0mm)	6" (152mm)	6" (152mm)	44" (1118mm)	35" (889mm)

Electrical Requirements	kW Loading 240V/208V	Three Phase (only) Nominal Amperes Per Line For Each Circuit					
<b>NOTE: Two Circuits Required</b>	20.8 Total 10.4 (per Circuit)	240V			208V		
		X	Y	Z	X	Y	Z
		28	22	28	32	26	32

208 VAC = 197 VAC to 219 VAC 240 VAC = 220 VAC to 252 VAC

# AIR PAC

