



Model G80-30B

Specifications:

Garland G80 Series Char Broiler, model _____, available in 18" (457mm), 24" (610mm), 30" (762mm), 36" (914mm), and 48" (1219mm) widths. Stainless steel front and painted sides. Cast iron dual sided rack sections with 1/2" (13mm) rounded bar (broad) and diamond (fine) patterns on opposite sides in increments of 6" (152mm) sections. AGA/CGA approved, NSF Listed.


Standard Features:

- 15,000 BTU/hr. per burner. One burner per 6" of width
- Individual burner controls
- Stand-by pilots for instant lighting
- Stainless steel front, black powder-coat epoxy sides and rear
- 4" (102mm) legs with adjustable feet, (not shown)
- Ceramic briquettes
- Dual sided cast iron broiler racks, with 1/2" (13mm) rounded bar (broad) and diamond (fine) patterns on opposite sides, in of 6" (152mm) sections.
- Gas pressure regulator

Optional Features:

- Stainless steel sides
- Diamond branding rack in lieu of standard rack, No Charge, specify when ordering.
- Optional multiple broiler lengths available by ordering 24" and 36" models with modified sides
- Stainless steel spatterguard
 - Holding shelf for spatterguard

Optional CS80 Floor stand:

- Floor Stands: Heavy-duty stands of open design with seamless welded square tube leg and black finish in five (5) widths for all broilers. Specify width when ordering (i.e. 24" (610mm) wide stand is CS80-24)
 - Optional: Stainless steel finish
 - Swivel casters W/front brakes; set of 4



Garland Commercial Industries, Inc.
 185 East South Street
 Freeland, Pennsylvania 18224
 Phone: (570) 636-1000
 Fax: (570) 636-3903

Garland Commercial Ranges Ltd
 1177 Kamato Road, Mississauga, Ontario
 L4W 1X4 CANADA
 Phone: 905-624-0260
 Fax: 905-624-5669

Enodis UK LTD
 Swallowfield Way, Hayes, Middlesex
 UB3 1DQ ENGLAND
 Telephone: 081-561-0433
 Fax: 081-848-0041

| MODEL | Width: In (mm) | Depth: In (mm) | Height: In (mm) | No. of Burners | Total Input (BTU/Hr) | Ship Weight lbs./kg |
|---------|----------------|----------------|-----------------|----------------|----------------------|---------------------|
| G80-18B | 18 (457) | 31-1/4 (794) | 22 (559) | 3 | 45,000 | 190/86 |
| G80-24B | 24 (610) | 31-1/4 (794) | 22 (559) | 4 | 60,000 | 220/98 |
| G80-30B | 30 (762) | 31-1/4 (794) | 22 (559) | 5 | 75,000 | 265/120 |
| G80-36B | 36 (914) | 31-1/4 (794) | 22 (559) | 6 | 90,000 | 330/150 |
| G80-48B | 48 (1219) | 31-1/4 (794) | 22 (559) | 8 | 120,000 | 375/170 |

NOTE: Installation clearance reductions are applicable only where local codes permit.

When ordering specify gas type, natural or propane and elevation if over 2,000 ft (610m).

| Operating Manifold Pressure | |
|-----------------------------|---------------|
| Natural | Propane |
| 6"WC (15mbar) | 9"WC (22mbar) |
| Installation Clearances | |
| Sides | Rear |
| 6" (152mm) | 6" (152mm) |

Garland products are not approved or authorized for home or residential use, but are intended for commercial applications only. Garland will not provide service, warranty, maintenance or support of any kind other than in commercial applications.

