



*Model GD-15*

*(Shown with Optional Stainless Steel Sides)*

### Specification:

Gas designer series fryer, Model GD-15F; 15" (381mm) wide, 24" (610mm) deep x 20" (508mm) high, easy clean design, with stainless steel front and black painted sides. Steel frypot with open pot design, 15 lbs. shortening capacity and deep cold zone. Exclusive 1° F snap action thermostat. Piezo spark ignition, natural or propane gas, 45,000 total BTU input. Designed as free standing or to be banked with other GD series equipment.

### Standard Features:

- Stainless steel front and black painted sides
- 4" (102mm) Sanitary legs
- Easy clean features
- 18" (457mm) deep cooking surface
- Open pot design, no tubes
- Deep cold zone, keeps contaminants out of cooking area, extending shorting life
- Cold rolled steel frypot
- 15 lbs shortening capacity
- 100% safety system
- 1° F snap action thermostat
- Piezo spark ignition
- Rear gas connection w/pressure regulator
- Natural or propane gas
- 45,000 total BTU
- Twin fryer baskets

### Optional Features:

- Stainless steel sides
- Stainless steel back and bottom

### Optional CSD-GF Stand:

- Floor Stands: Heavy-duty stands of open design with seamless welded square tube leg and black finish storage shelf. Working height of all units on stands 35-1/2" (902mm). Stand widths of 15" (381mm), Each unit must have its own stand.
  - Optional: Stainless steel finish
  - Swivel casters W/front brakes; set of 4



**Garland Commercial Industries, Inc.**  
 185 East South Street  
 Freeland, Pennsylvania 18224  
 Phone: (570) 636-1000  
 Fax: (570) 636-3903

**Garland Commercial Ranges Ltd**  
 1177 Kamato Road, Mississauga, Ontario  
 L4W 1X4 CANADA  
 Phone: 905-624-0260  
 Fax: 905-624-5669

**Enodis UK LTD**  
 Swallowfield Way, Hayes, Middlesex  
 UB3 1DQ ENGLAND  
 Telephone: 081-561-0433  
 Fax: 081-848-0041

MODEL	Over All Dimensions			Total Input BTU/Kw	Shipping Wt Lb/kg
	Width	Height	Depth		
GD-15F	15" (381mm)	20" (508mm)	24" (610mm)	45,000/13.2	120/54

Gas Input ratings shown here are for installations up to 2,000 ft. (610m) above sea level. Specify altitudes over 2,000 ft.

Garland products are not approved or authorized for home or residential use, but are intended for commercial applications only. Garland will not provide service, warranty, maintenance or support of any kind other than in commercial applications.

Clearances To Combustible Wall		Floor or Base
Sides	Back	
6" (152mm)	6" (152mm)	Non Combustible

Manifold Inlet Size NPT	Manifold Operating Pressure			
	Natural		Propane	
	"WC	mbar	"WC	mbar
1/2"	4.2	10.5	9	22.4

