



Item #: _____

Models: M43-FTR, M43-FTS, M43-FTT

Product Name: Master Series Combination Open Burner Top & French Top Range



Model M43FTR

Specification:

Heavy duty gas range with oven, Model M43-FTR. Combination top, three (3) open Starfire burners at front, 18,000 BTU (5.3kW) each. Heavy duty cast iron top grates/ring grates. Three (3) heavy duty cast iron French tops at rear 11-1/4" (286mm) wide x 14-3/4" (375mm) deep, with one 15,000 BTU (44kW) Starfire burner per French plate. All top burners controlled with On/Off valve 34" (864mm) wide x 38" (965mm) deep, including 7-1/2" (191mm) deep stainless steel front rail. Porcelain enamel oven interior measuring 26-1/4" (667mm) wide x 13 1/2" (343mm) high x 29" (737mm) deep. 40,000 BTU (11.72kW) cast iron oven burner. Stainless steel front with black powder coat epoxy sides. Natural or propane gas. CSA, C/US certified and NSF listed. (Also available with storage base with doors, Model M43-FTS, and modular top, Model M43-FTT).

Standard Features:

- Stainless steel front, black powder coat epoxy sides.
- 6" (152mm) chrome steel adjustable legs
- 7-1/2" (191mm) stainless steel front rail
- (3) 18,000 BTU (5.3kW) Starfire open burners
- (3) 15,000 BTU (4.4kW) Starfire French top burners
- Removable ring grates over open burners at front
- Cast iron top grates
- One piece stainless steel drip tray
- (3) Solid removable cast iron French top plates at rear
- Piezo Spark ignition for oven
- Fully porcelainized oven interior
- 40,000 BTU (11.72kW), natural gas; 35,000 (19.25kW), propane, cast iron oven burner
- Storage base of aluminized steel
- One year limited parts & labor warranty (USA & Canada)

Optional Features:

- Stainless steel left, right or both sides or main back
- Stainless steel common front rail up to 68" (1728mm) wide (two or more units in a battery)
- Fully grooved griddle (or grooved sections)
- Stainless steel oven interior
- Convection oven base, add C to model #, e.g. M43-FTRC
- Additional oven rack
- Rear gas connection, 3/4" or 1" NPT
- End caps and cover (no charge) - Must specify
- Swivel casters (4) with front brakes
- Polyurethane non-marling swivel casters w/ front brakes
- 6" (152mm) stainless steel adjustable legs
- 4" (102mm) chrome steel adjustable legs
- Toe base (not for use with RC oven base)
- Storage base shelf of aluminized or stainless steel
- Single deck stainless steel tubular high shelf
- Double deck stainless steel tubular high shelf
- 10" (254 mm) high stainless steel backguard
- 17" (432mm) high stainless steel backguard
- 33" (838mm) high stainless steel backguard
- Stainless steel vertical flue riser, 13"W x 33"H, (330mm x 839mm)
- E-model suffix- electric spark ignition on all pilots for MST models only, e.g. MS43-FTRE
- 230 volt, 50 cycle components, RC motor and/or electric ignition (export)
- Celsius dial for oven thermostat (no charge)

NOTE: Ranges supplied with casters must be installed with an approved restraining device.



Garland Commercial Industries, Inc.
185 East South Street
Freeland, Pennsylvania 18224
Phone: (570) 636-1000
Fax: (570) 636-3903

Garland Commercial Ranges Ltd
1177 Kamato Road, Mississauga, Ontario
L4W 1X4 CANADA
Phone: 905-624-0260
Fax: 905-624-5669

Enodis UK LTD
Swallowfield Way, Hayes, Middlesex
UB3 1DQ ENGLAND
Telephone: 081-561-0433
Fax: 081-848-0041

GARLAND® GAS Master Series Combination Open Burner Top & French Top Range M43-FTR, FTS, FTT



Item #: _____
 Models: M43-FTR, M43-FTS, M43-FTT
 Product Name: Master Series Combination Open Burner Top & French Top Range

Product	Width: In(mm)	Depth: In(mm)	Height: In(mm) (w/ NSF Legs)	Height: In(mm) (w/o NSF Legs)	Oven/Storage Base Interior: in(mm)		
					Width	Depth	Height
M43-FTR	34(864)	38(965)	36-3/8(924)	30-3/8(772)	26-1/4(667)	29(737)**	13-1/2(343)
M43-FTS	34(864)	38(965)	36-3/8(924)	36-3/8(924)	26(665)	30-1/2(773)	20-1/2(519)
M43-FTT	34(864)	38(965)	36-3/8(924) w/stand	9-1/2 (241) w/o stand*	N/A	N/A	N/A

*Modular top has 1-1/2" seating flanges. **RC oven is 25"(635mm) deep.

INPUT-BTU/hr (Natural Gas)	M43FTR	M43FTRC	M43FTS & M43FTT
6 Top Burners			
3@18,000***(Open Top) 3 @ 15,000(Hot Top)	99,000(29.00kW)	99,000(29.00kW)	99,000(29.00kW)
BTU Oven***	40,000(11.72kW)	37,000(10.84kW)	N/A
TOTAL	139,000(40.72kW)	136,000(39.84)kW	99,000(29.00kW)

RC=Range w/Convection Oven R=Range w/Oven S=Range w/Storage Base T=Modular Top
 *** Open Top Burner rated 16,000 BTU (4.69kW) and Oven Rated 35,000 BTU (10.25kW) for Propane gas

INSTALLATION NOTES			Shipping Wt: (Lb/Kg)
Combustible Wall Clearances ¹	Entry Clearances	Operating Pressure	M43-FTR 440/200
Sides: 11" (279mm) Back: 6" (152mm)	Crated: 39-1/4" (997mm) Uncrated: 34-1/4" (870mm)	Natural: 6" WC (15mbar) Propane: 10" WC (25mbar)	M43-FTS 340/155
			M43-FTT 250/114

